

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 10W-40 with Moly MOTORCYCLE OIL

**PRODUCT # 10777**

**API Service SJ, JASO MB**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>34.2</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>0.854</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.12</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>98</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>14.2</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>160</b>
<b>Color</b>		<b>Amber</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>450</b>
<b>CCS @ -25°C, CPS</b>	<b>D-5293</b>	<b>7,000 Max</b>
<b>MRV TP-1 @ -30°C, CPS</b>	<b>D-4684</b>	<b>60,000 Max</b>

**Lucas Synthetic SAE 10W-40 with Moly API SJ, JASO MB Motorcycle Oil is a blend of high quality synthetic base oils and an exclusive high performance additive package that lowers oil temperatures, extends oil and component life, reduces noise and reduces leaks.**

**Our unique moly chemistry provides maximum friction reducing properties in severe racing conditions. Provides wear protection at start-up and has excellent cold temperature properties. Not recommended for use in wet clutch applications. For use in all air-cooled and water/radiator cooled 4-stroke engines. BAJA TESTED.**