

TECHNICAL DATA SHEET



SYNTHETIC SAE 0W-40

EUROPEAN FORMULA

PRODUCT # 10210, 10211, 10212, 10213, 10214, 10215

TEST

ASTM

TYPICAL

API Gravity	D-1298	35.18
Specific Gravity @ 60°F	D-1298	0.850
Density @ 60°F, lb/gal	D-1298	7.08
CCS @ -35°C, CPS	D-5293	6,200 Max
MRV @ -40°C, CPS	D-4684	60,000 Max
Zinc, WT%	X-ray	0.085
TBN, Mg KOH/g	D-2896	7.5
Viscosity @ 40°C cSt	D-445	75.1
Viscosity @ 100°C cSt	D-445	14.4
Viscosity Index	D-2270	173
Flash Point, COC °F	D-92	445
Color		Light Brown

Lucas Synthetic SAE 0W-40 Motor Oil is especially formulated for high mileage or high performance engines; it is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas Synthetic SAE 0W-40 Motor Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

Lucas Synthetic SAE 0W-40 Motor Oil is the perfect lubricant for high RPM and high temperature engines. The exclusive additive package in Lucas Synthetic SAE 0W-40 Motor Oil allows for extended drain intervals.

Lucas Synthetic SAE 0W-40 Motor Oil far exceeds all OEM specifications. Formulated to meet ALL motor that calls for a Synthetic SAE 0W-40 motor oil.

Meets or exceeds American and European OEM specifications API SN/SM/SL/SJ/CF, ACEA A5/B5-04, A3/B4-04, C2-08, C3-07, C2-04, MB 229.31, MB 229.51, VW 50200, 50500, 50501, BMW Longlife-04, Porsche, Ford WSS M2 C 917 A. Suitable for use where VW 50700 is recommended.